

In the Claims

1. (Currently Amended) A flat display apparatus comprising:
a flat display panel displaying an image;
5 a first receiving container receiving the flat display panel;
a driving part disposed on the first receiving container to drive a part of the flat display
panel apparatus;

a second receiving container covering the driving part to block an electromagnetic
radiation ~~radiated~~ radiating from the driving part; and

10 a ground member including a first embossed pattern protruding from a surface of
~~formed with~~ the second receiving container, wherein the ground member is disposed between
the first receiving container and the second receiving container to electrically connect the first
receiving container to the second receiving container.

15 2. (Original) The flat display apparatus of claim 1, wherein the driving part
comprises a printed circuit board (PCB) that applies an electric signal to the flat display panel.

3. (Currently Amended) The flat display apparatus of claim 2, wherein the
second receiving container comprises a bottom surface, ~~a sidewall protruded~~ and sidewalls
20 protruding from a side of the bottom surface and to define a receiving space ~~defined by the~~
~~sidewall to receive~~ for the printed circuit board (PCB), and wherein the ground member is
disposed between the ~~sidewall~~ at least one of the sidewalls and the first receiving container.

4. (Currently Amended) The flat display apparatus of claim 3, ~~wherein the~~
25 ~~sidewall comprises~~ further comprising an extended portion that extends from the sidewalls is

extended in a plane ~~direction in~~ substantially parallel ~~to~~ with the bottom surface ~~from an end~~
~~portion opposite to the bottom surface, and~~ wherein the ground member is disposed on the
extended portion.

5 5. (Canceled)

6. (Withdrawn) The flat display apparatus of claim 3, wherein the ground
member comprises an extended protrusion.

10 7. (Currently Amended) The flat display apparatus of claim 1, further comprising
a backlight assembly including a lamp assembly that generates a light, an optical sheet
assembly that improves ~~an~~ optical characteristics of the light generated from the lamp, and
wherein the flat display panel comprises a liquid crystal display (LCD) panel receiving the
light that passes through the optical sheet assembly to display an image by using a liquid
15 crystal disposed between substrates of the liquid crystal display panel.

8. (Original) The flat display apparatus of claim 7, wherein the driving part
comprises an inverter that drives the lamp assembly.

20 9. (Currently Amended) The flat display apparatus of claim 7, wherein the
second receiving container comprises a bottom surface, ~~a sidewall protruded~~ and sidewalls
protruding from ~~a side of~~ the bottom surface and to define a receiving space ~~defined by the~~
~~sidewall to receive~~ for receiving the inverter, and wherein the ground member is disposed
between ~~the sidewall~~ at least one of the sidewalls and the first receiving container.

25

10. (Original) The flat display apparatus of claim 9, wherein the ground member comprises an embossed pattern.

11. (Withdrawn) The flat display apparatus of claim 9, wherein the ground member comprises an extended protrusion.

12-16. (Canceled)

17. (Currently Amended) A flat display apparatus comprising:

10 a display unit displaying an image;

a backlight assembly disposed under the display unit to supply the display unit with a light;

a bottom chassis disposed under the backlight assembly to receive the display unit and the backlight assembly;

15 an inverter disposed under the bottom chassis to apply an electric signal and an electric power to the backlight assembly;

an inverter case disposed under the bottom chassis, the inverter case including a bottom surface, ~~a sidewall protruding~~ and sidewalls protruding from a side of the bottom surface and to define a receiving space defined by the sidewall to receive for the inverter, the

20 inverter case to blocking an electromagnetic radiation generated from the inverter; and

a ground member including embossed patterns protruding from a surface of ~~formed~~ with the inverter case, the ground member being disposed between at least one of the sidewall ~~sidewalls~~ and the bottom chassis to electrically connect the inverter case to the bottom chassis.

18. (Currently Amended) The flat display apparatus of claim 17, wherein the ~~sidewall comprises~~ sidewalls comprise an extended portion that extends ~~is extended~~ in a plane ~~direction in parallel to~~ with the bottom surface ~~from an end portion opposite to the bottom surface~~, and the ground member is disposed on the extended portion.

5

19. (Currently Amended) The flat display apparatus of claim 17, wherein the ground member comprises ~~an embossed pattern or~~ an extended protrusion.

20. (Original) The flat display apparatus of claim 17, further comprising a mold
10 frame disposed between the backlight assembly and the bottom chassis to support the backlight assembly.

21. (New) A flat display apparatus comprising:
a flat display panel displaying an image;
15 a first receiving container receiving the flat display panel;
a driving part disposed on the first receiving container to drive the flat display panel;
a second receiving container covering the driving part to block electromagnetic
radiation radiating from the driving part, the second receiving container including:

a bottom surface,
20 sidewalls extending from edges of the bottom surface, and
an extended portion extending from the sidewalls; and
a ground member protruding from a surface of the extended portion, the ground
member being disposed between the first receiving container and the second receiving
container to electrically connect the second receiving container to the first receiving container.

25

22. (New) The flat panel display apparatus of claim 21, wherein the ground member comprises an embossed pattern or an extended protrusion.